

# TELEMATICS MODULE

Tested and Certified

HVAC + R


STANDARD

CABIN / MUX



Certified

N° 00965-21-13681



## MAIN FUNCTIONS

DATA LOGGER

FLEET TRACKING

REMOTE CONTROL

CONNECTIVITY

DIAGNOSTICS

SERVICE ALERTS

MAINTENANCE

CONFIGURATIONS

## CHARACTERISTICS

- Preventive maintenance alerts with customized individual hourmeters
- **Data Logging:** Records faults with date and time stamp - geolocation also possible
- **Remote Diagnostics:** View faults, status and events in real time from your smartphone, tablet or PC
- **Increased operational efficiency:** Remote system configuration - local configuration lock option
- Real-time clock
- Can bus (2 ports) - SAE J1939
- One Wire
- 2 to 8GB flash memory for Data Logger


## AVAILABLE FOR



# TECHNICAL DATA



Approximated weight: 100g



## CONNECTORS



MINI-FIT MOLEX 12 VIAS  
Part Number: 39-01-2120  
TERMINAL  
Manufacturer: MOLEX  
PN: 39-00-0038

TECHNICAL DATA	
OPERATING VOLTAGE	12 Vdc to 24 Vdc
VOLTAGE RANGE	10 Vdc to 30 Vdc
MAXIMUM VOLTAGE	32 Vdc during 5min
MAXIMUM CURRENT PER OUTPUT	N/A
OUTPUT SHORT-CIRCUIT	N/A
REVERSE POLARITY	YES
OPERATING TEMPERATURE	-40°C to +85°C / -40°F to +185°F
STORAGE TEMPERATURE	-40°C to +85°C / -40°F to +185°F
TEMPERATURE SENSOR	N/A
PROTECTION DEGREE	IP 30
CONNECTOR	MOLEX MINI FIT
WIRELESS COMMUNICATION	BLUETOOTH and WI-FI
WIRED COMMUNICATION	ONE Wire and CAN Bus
MAXIMUM CURRENT CONSUMPTION	60mA @12v / 40mA @24V *
STANDBY CONSUMPTION	N/A *

\* According to product configuration. \*\* Consumption may vary according to customer specifications.  
We keep the right to update or change information regarding products without prior notice.

## CONFIGURATION OPTIONS

INPUTS: Two inputs (Analog and/or Digital)

## FUNCTIONS UNDER REQUEST



WI-FI\*



BLUETOOTH\*



CELL PHONE  
INTERFACE\*



CAN BUS



DATA  
LOGGER\*

\*Through Globus Way module. \*\*Through 3G/4G module.

