







HVAC

3 SPEED VENTILATION AND PROPORTIONAL TEMPERATURE **CONTROL PANEL**


GL-P8HGL201

CHARACTERISTICS

- 3 speed evaporator power switch 16A@12V and 10A@24V
- Proportional hot water valve control
- · Fresh air output
- 500mA negative clutch output
- · A/C button
- Fresh air button
- Diagnostic LED

- Innovative design
- Designed for heavy-duty applications
- Analog commands
- · Backlit buttons and symbols
- Customer logo on the panel (optional)
- Screwless installation
- Automotive connector
- High frontal protection grade- IP 54

TECHNICAL DATA



Approximate gross weight: 175 g

14.5mm 0.57in 8.0mm 0.31in 24.7mm 0.97in

Î GL-P8HGL201

CONNECTORS



3 Speed Power switch Part Number: 754C3 Manufacturer: KOCH SALES



Mate-N-Lok 15 cable paths Part Number: 1-480710 -Terminal - PN: 350689-3 Manufacturer: Tyco Electronics

TECHNICAL DATA

OPERATING VOLTAGE 12 Vdc to 24 Vdc

VOLTAGE RANGE 9 Vdc to 30 Vdc

MAXIMUM VOLTAGE 32 Vdc during 5min

MAXIMUM OUTPUT CURRENT See description above

Protected *** **OUTPUT SHORT CIRCUIT**

REVERSE POLARITY Protected *

OPERATING TEMPERATURE -40°C to +85°C /-40°F to +185°F

-40°C to +125°C /-40°F to +257°F STORAGE TEMPERATURE

TEMPERATURE SENSOR N/A

FRONTAL PROTECTION DEGREE IP 54

COMMUNICATION N/A

MAXIMUM CURRENT CONSUMPTION 40mA @ 12Vdc, 20mA @ 24Vdc **

We keep the right to update or change information regarding products without prior notice.

FD0025 FOLDER NEO P8HGL201_ING REV.1











^{*} According to product specifications.

Consumption ,may vary according to customer specifications.

^{***} Except on power switch.