







HVAC


DOUBLE PID 3 SPEED VENTILATION AND TEMPERATURE CONTROL PANEL GL-P8HGL211

CHARACTERISTICS


- 3 speed evaporator power switch 16A@12V and 10A@24V
- Proportional hot water valve control
- Return temperature sensor
- Duct temperature sensor
- Celcius scale
- Fresh air output
- 5A positive clutch output
- A/C button


- Fresh air button
- Diagnostic LED
- Innovative design
- Designed for heavy-duty applications
- Analog commands
- Backlit buttons and symbols
- Customer logo on the panel (optional)
- Screwless installation
- Automotive connector
- High frontal protection grade- IP 54

TECHNICAL DATA



Approximate gross weight: 175 g





CONNECTORS



3 Speed Power switch Part Number: 754C3 Manufacturer: KOCH SALES



Mate-N-Lok 15 cable paths Part Number: 1-480710 -Terminal - PN: 350689-3 Manufacturer: Tyco Electronics

TECHNICAL DATA

OPERATING VOLTAGE 12 VDC to 24 VDC

9 VDC to 30 VDC **VOLTAGE RANGE**

MAXIMUM VOLTAGE 32 VDC during 5min

MAXIMUM OUTPUT CURRENT See description above

Protected *** **OUTPUT SHORT CIRCUIT**

REVERSE POLARITY Protected *

OPERATING TEMPERATURE -40°C to +85°C /-40°F to +185°F

-40°C to +125°C /-40°F to +257°F STORAGE TEMPERATURE

NTC 10K **TEMPERATURE SENSOR**

FRONTAL PROTECTION DEGREE **IP 54**

COMMUNICATION N/A

MAXIMUM CURRENT CONSUMPTION 40mA @ 12VDC, 20mA @ 24VDC **

- * According to product specifications.
- ** Consumption ,may vary according to customer specifications.
- *** Except on power switch.

We keep the right to update or change information regarding products without prior notice.

ED0035 FOLDER NEO P8HGL211 ING REV 2







